



ED150 iFlex
15 inch touch pos system
Exclusive design, patented product



OEM&ODM&SERVICE

Specification :

SYSTEM	ED150 iFlex
Processor	Intel Celeron J1900 Quad-Core, Up to 2.42Ghz Intel Celeron J3455 Quad-Core, Up to 2.30 GHz Intel Celeron J4125 Quad-Core, Up to 2.70 GHz Intel Core i3/i5 3rd, 4th, 5th, 6th, 7th, 8th High Performance CPU
OS	Windows 7, 10, 11, POSReady7
Memory Support	DDR 4/8/16G
Hard Driver	32G/64G/128G/256G
DISPLAY	
LED panel Size	15 inch TFT LED/LCD
Resolution	1024*768
Brightness	300cd/m2
Touch Screen	Main screen 10 point Capacitive touch screen (default)
INTERFACE	
I/O port	1* power button
	1*VGA/HDMI
	1*COM(RS232)
	LAN:RJ-45*1
	4*USB2.0 2* USB 3.0
	Audio out*1 MIC IN*1
Power adapter	Input AC 100~240V/50~60hz, Output DC12V/5A
Functions	
2nd Display	9.7 inch (Touch on 2nd display Option)
VFD	VFD 220 Customer Display
MSR	ISO 3 Tracks Reading
Wifi	IEEE 802.11 a/b/g/n/ac, 2.4Ghz (5.0Ghz option)
Bluetooth	Bluetooth 4.0 protocol
Speaker	1*4Ω*3W Speaker
Wall Mount	VESA 75*75mm (Available for Single Display Only)
CERTIFICATE	FCC Class A/CE Mark/LVD/CCC

