edobbo

OEM&ODM&SERVICE

- **Aluminum Alloy Case**

All aluminum alloy shell, more stable and waterproof

- **Thin and fashionable**

EDA152 has a 15 inch PCAP touch screen with streamlined structure, ultra-thin body and rich connection interface. The hidden interface and screw-free back cover design make EDA152 fashionable and elegant.

- **Quick installation and easy maintenance**

The back cover can be easily removed without any tools, making installation and maintenance faster, and greatly reducing maintenance time and labor costs.

edobbo

Specification：

SYSTEM	EDA152
Processor	Intel Celeron J1900 Quad-Core, Up to 2.42Ghz Intel Celeron J3455 Quad-Core, Up to 2.30 GHz Intel Celeron J4125 Quad-Core, Up to 2.70 GHz Intel Core i3/i5 3rd, 4th, 5th, 6th, 7th, 8th High Performance CPU
OS	Windows 7, 10, 11, POSReady7
Memory Support	DDR 4/8/16G
Hard Driver	32G/64G/128G/256G
DISPLAY	
LED panel Size	15 inch TFT LED/LCD
Resolution	1024*768
Brightness	300cd/m2
Touch Screen	Main screen 10 point Capacitive touch screen (default)
INTERFACE	
I/O port	1* power button
	1*VGA/HDMI
	1*COM(RS232)
	LAN:RJ-45*1
	4*USB2.0 2* USB 3.0
	Audio out*1 MIC IN*1
Power adapter	Input AC 100~240V/50~60hz, Output DC12V/5A
Functions	
2nd Display	9.7 inch (Touch on 2nd display Option)
VFD	VFD 220 Customer Display
MSR	ISO 3 Tracks Reading
Wifi	IEEE 802.11 a/b/g/n/ac, 2.4Ghz (5.0Ghz option)
Bluetooth	Bluetooth 4.0 protocol
Speaker	1*4Ω*3W Speaker
Wall Mount	VESA 75*75mm (Available for Single Display Only)
CERTIFICATE	FCC Class A/CE Mark/LVD/CCC